



## PDG-DXL2000



- Ultra-short Focus Projector with built-in 10 Watt speaker
- Throw ratio of 0.24 : 1 enables an 80" projection from a distance of merely 8.8 cm
- 3D-function for vivid visualisations without excessive space requirements
- Extremely low maintenance as a result of the integrated longlife-filters
- 6-segment color wheel
- XGA resolution (1,024 x 768 pixels) in 4 : 3 format
- Brightness: 2,000 ANSI lumens (dynamic mode), contrast ratio: 2,000 : 1
- Network control via RJ45 (LAN)
- 3 years warranty, 1-years lamp warranty (max. 2,000 hours)

# PDG-DXL2000

TECHNICAL DATA	PDG-DXL2000
EAN Code	4994334284860
Category	Business & Education
Panel	1 x 0.55 " DMD Chip (4:3)
Lamp	275 W NSH (LMP-143)
Brightness	2000 ANSI lumens, 1550 ANSI lumens (eco mode)
Lamp life	3000 h (eco mode) / 2000 h (normal mode)
Fan noise	28 dB (eco mode) / 36 dB (normal mode)
Standard lens	F = 2.5 / f = 4.83 mm *
Throw distance ratio	0.24 : 1
Throw distance	-0.045 - 0.141 m
Contrast ratio	2000 : 1
Resolution in pixels	1,024 x 768 (XGA)
Image size min. - max. (diagonal)	55 - 90 inch
Uniformity	80 %
Bandwidth/Frequency	150 MHz, Horizontal frequency: 15 - 93 kHz, Vertical frequency: 50 - 120 Hz
Color systems	PAL, SECAM, NTSC, NTSC4.43, PAL-M/N
Connections	Input 1: HDMI (HDCP) Input 2: D-Sub15 (RGB/component/S-Video) Input 3: D-Sub15 (RGB) or monitor out Input 4: RCA (composite) Input 5: Mini DIN 4 (S-Video) Audio: 2 x RCA (R/L mono) Audio: 2 x 3.5 mm stereo jack Audio output : 3.5 mm stereo jack Control input jack 1: D-Sub9 (RS232) Control input jack 2: RJ45 (LAN) Control input jack 3: Mini DIN 3 (3D function)
Audio function	10 W mono
Keystone correction	vertical +/- 5°
HDTV compatibility	480i, 480p, 575i, 575p, 720p, 1,080i, 1,080p
Computer compatibility	UXGA, SXGA, SXGA+, WXGA, XGA, SVGA, VGA, Mac, WUXGA
Zoom/Focus	-/manual
Power consumption / Voltage	305 W (eco mode) / 375 W (normal mode) / 0.85 W (stand-by mode) / 100 - 240 V
Unique features	Longlife-filter, 3D function, Eco mode, Power management, Automatic set-up (input search, keystone-correction, auto PC adjustment), Direct Power On/Off, Color-board mode, Color management function, MyLogo function, Freeze function, No Show mode, Picture reverse function, Picture inverse function, Key lock function, PIN code lock, Kensington lock, Presentation timer, Web management function, Email error reporting, SNMP log function, Multi language menu
Warranty	3 years, 24-hr replacement service (D/CH/I/F - except overseas), 1-year lamp warranty (max. 2,000 hours)
Dimensions (W x H x D)	321 x 178 x 386 mm
Weight (net)	6.2 kg
Standard accessories	IR remote control, Batteries, User manual, Power cable, D-Sub15 cable, PIN code label
Optional accessories	SCART/D-Sub15 cable (POA-CA-SCART) Wall mount (POA-CH-EX06)
Lenses	Standard lens

\* You can use the distance calculator at [www.sanyo.de](http://www.sanyo.de) to determine exact image sizes and distances

Technical specifications subject to change without notice. Date 09/2010

